



## Function

The manual destacker is an ideal aid for manual sheet handling. It is a permanent magnet system which, due to its multipole division and narrow pole spacing, ensures that only one sheet is lifted from the stack at a time. The manual destacker is therefore ideal for lifting and separating individual sheets. We recommend it for destacking sheets up to 2 mm thick.

## Design and delivery forms

The narrow-pole permanent magnet system is housed in a robust aluminum housing. This housing has two wide lugs on the side, into which a strap made of leather – or optionally of plastic – is inserted. A thumb strap attached to the hand straps provides additional stability.

## Use

The manual destacker is slipped over the working glove with the help of hand and thumb straps and is thus securely fixed in the palm of the hand without interfering. To lift a sheet from the stack, the user places the manual destacker flat on one corner of the sheet. This is attracted by the magnet and can be easily lifted off or pushed over the edge of the stack. The sheet can then be gripped and transported by hand. The manual destacker can be easily removed from the sheet metal with a twisting hand movement.

### General information

The statements are in no way to be deemed as an advisory service of our company, but are only descriptive without guaranteeing or granting property-related qualities. Liability on the basis of the statements of this product information is specifically excluded, unless compelling legal liability facts are evident. All information is correct to the best of our knowledge, but no responsibility will be taken for any errors. We reserve the right to make technical changes. Reproduction in any form, including extracts, only with the express permission of thyssenkrupp Magnettechnik.



When working with metal sheets, it is essential to wear protective gloves!

## Contact

thyssenkrupp Magnettechnik  
Branch of thyssenkrupp Schulte GmbH  
Johanniskirchstr. 71  
45329 Essen, Germany  
T: 0800 624 6387 (from Germany), +49 201 946161-558 (international)  
F: +49 201 946161-555  
[www.thyssenkrupp-magnettechnik.com](http://www.thyssenkrupp-magnettechnik.com)  
[magnet@thyssenkrupp-materials.com](mailto:magnet@thyssenkrupp-materials.com)