


# Stabstahl

<b>EN 10025</b>	Technische Lieferbedingungen
<b>EN 10279 (DIN 1026-1)</b>	Maße und zulässige Abweichungen

## U-Stabstahl, rundkantig S235JR (W.-Nr. 1.0038)

UNP mit geneigten inneren  
Flanschlflächen  
Herstellungslängen  
6.000 mm

Abmessung mm (h x b x s)	Gewicht kg/m	Abwicklung m <sup>2</sup> /m	Abmessung mm (h x b x s)	Gewicht kg/m	Abwicklung m <sup>2</sup> /m
30 x 33 x 5,0	4,40	0,174	50 x 38 x 5,0	3,98	0,232
40 x 20 x 5,0	5,02	0,142	60 x 30 x 6,0	5,22	0,215
40 x 35 x 5,0	2,96	0,199	65 x 42 x 5,5	7,30	0,273
50 x 25 x 5,0	5,76	0,181			




Auch in S355J2 lieferbar.

# Stabstahl

**EN 10025** Technische Lieferbedingungen  
**EN 10058** (DIN 1017) Maße und zulässige Abweichungen

## Flachstahl S235JR (W.-Nr. 1.0038)

Abmessung mm (b x a)	Gewicht kg/m	Abmessung mm (b x a)	Gewicht kg/m
10 x 5	0,393	40 x 5	1,570
12 x 5	0,471	6	1,880
6	0,565	8	2,510
8	0,754	10	3,140
15 x 5	0,589	12	3,770
6	0,707	15	4,710
8	0,942	20	6,280
10	1,180	25	7,850
16 x 5	0,628	30	9,420
6	0,754	45 x 5	1,770
8	1,000	6	2,120
10	1,260	8	2,830
18 x 5	0,707	10	3,530
6	0,848	12	4,240
8	1,130	15	5,300
10	1,410	20	7,070
12	1,700	25	8,830
20 x 5	0,785	30	10,600
6	0,942	50 x 5	1,960
8	1,260	6	2,360
10	1,570	8	3,140
12	1,880	10	3,930
15	2,360	12	4,710
25 x 5	0,981	15	5,890
6	1,180	20	7,850
8	1,570	25	9,810
10	1,960	30	11,800
12	2,360	40	15,700
15	2,940	55 x 5	2,160
20	3,930	6	2,590
30 x 5	1,180	8	3,450
6	1,410	10	4,320
8	1,880	12	5,180
10	2,360	15	6,480
12	2,830	20	8,640
15	3,530	25	10,800
20	4,710	30	13,000
25	5,890	60 x 5	2,360
35 x 5	1,370	6	2,830
6	1,650	8	3,770
8	2,200	10	4,710
10	2,750	12	5,650
12	3,300	15	7,070
15	4,120	20	9,420
20	5,500	25	11,800
25	6,870	30	14,100




Auch in S355J2 lieferbar.

# Stabstahl

EN 10025 Technische Lieferbedingungen  
 EN 10058 (DIN 1017) Maße und zulässige Abweichungen

## Flachstahl S235JR (W.-Nr. 1.0038)



Auch in S355J2 lieferbar.


Abmessung mm (b x a)	Gewicht kg/m	Abmessung mm (b x a)	Gewicht kg/m
60 x 35	16,500	80 x 60	37,700
40	18,800	90 x 5	3,530
50	23,600	6	4,240
65 x 5	2,550	8	5,650
6	3,060	10	7,070
8	4,080	12	8,480
10	5,100	15	10,600
12	6,120	20	14,100
15	7,650	25	17,700
20	10,200	30	21,200
25	12,800	35	24,700
30	15,300	40	28,300
40	20,400	50	35,300
70 x 5	2,750	60	42,400
6	3,300	100 x 5	3,930
8	4,400	6	4,710
10	5,500	8	6,280
12	6,590	10	7,850
15	8,240	12	9,420
20	11,000	15	11,800
25	13,700	20	15,700
30	16,500	25	19,600
35	19,200	30	23,600
40	22,000	35	27,500
50	27,500	40	31,400
75 x 5	2,940	50	39,300
6	3,530	60	47,100
8	4,710	110 x 5	4,320
10	5,890	6	5,820
12	7,070	8	6,910
15	8,830	10	8,640
20	11,800	12	10,400
25	14,700	15	13,000
30	17,700	20	17,300
80 x 5	3,140	25	21,600
6	3,770	30	25,900
8	5,020	40	34,500
10	6,280	50	43,200
12	7,540	120 x 5	4,710
15	9,420	6	6,020
20	12,600	8	7,540
25	15,700	10	9,420
30	18,800	12	11,300
35	22,000	15	14,100
40	25,100	20	18,800
50	31,400	25	23,600

# Stabstahl

EN 10025 Technische Lieferbedingungen  
 EN 10058 (DIN 1017) Maße und zulässige Abweichungen

## Flachstahl S235JR (W.-Nr. 1.0038)

Abmessung mm (b x a)	Gewicht kg/m	Abmessung mm (b x a)	Gewicht kg/m
120 x 30	28,300	140 x 15	16,500
40	37,700	20	22,000
50	47,100	25	27,500
60	56,500	30	33,000
130 x 5	5,100	40	44,000
6	6,410	50	55,000
8	8,160	150 x 5	5,870
10	10,200	6	7,020
12	12,200	8	9,420
15	15,300	10	11,800
20	20,400	12	14,100
25	25,500	15	17,700
30	30,600	20	23,600
40	40,800	25	29,400
50	51,000	30	35,300
140 x 5	5,500	40	47,100
6	6,670	50	58,900
8	8,790	60	70,700
10	11,000		
12	13,200		




Auch in S355J2 lieferbar.

# Stabstahl

<b>EN 10025</b>	Technische Lieferbedingungen
<b>EN 10060 (DIN 1013)</b>	Maße und zulässige Abweichungen

## Rundstahl S235JR (W.-Nr. 1.0038)




Auch in S355J2 lieferbar.

Abmessung mm (d)	Gewicht kg/m	Abmessung mm (d)	Gewicht kg/m
6	0,222	48	14,200
8	0,395	50	15,400
10	0,617	55	18,700
12	0,888	60	22,200
13	1,040	65	26,000
14	1,210	70	30,200
15	1,390	75	34,700
16	1,580	80	39,500
18	2,000	85	44,500
19	2,230	90	49,900
20	2,470	95	55,600
22	2,980	100	61,700
24	3,550	105	68,000
25	3,850	110	74,600
26	4,170	115	81,500
27	4,490	120	88,800
28	4,830	130	104,000
30	5,550	140	121,000
32	6,310	150	139,000
35	7,550	160	158,000
36	7,990	170	178,000
38	8,900	180	200,000
40	9,860	190	223,000
42	10,900	200	247,000
45	12,500		

<b>EN 10025</b>	Technische Lieferbedingungen
<b>EN 10059 (DIN 1014)</b>	Maße und zulässige Abweichungen

## Vierkantstahl S235JR (W.-Nr. 1.0038)



Auch in S355J2 lieferbar.


Abmessung mm (a)	Gewicht kg/m	Abmessung mm (a)	Gewicht kg/m
6	0,283	38	11,300
8	0,502	40	12,600
10	0,785	45	15,900
12	1,130	50	19,600
13	1,330	55	23,700
14	1,540	60	28,300
15	1,770	65	33,200
16	2,010	70	38,500
18	2,540	75	44,200
20	3,140	80	50,200
22	3,800	90	63,600
24	4,520	100	78,500
25	4,910	110	95,000
26	5,310	120	113,000
28	6,150	130	133,000
30	7,070	140	154,000
32	8,040	150	177,000
35	9,620		

# Stabstahl

**EN 10025** Technische Lieferbedingungen  
**EN 10055** (DIN 1024) Maße und zulässige Abweichungen

## T-Stahl S235JR (W.-Nr. 1.0038)


Abmessung mm (h x b x s)	Gewicht kg/m	Abmessung mm (h x b x s)	Gewicht kg/m
20 x 20 x 3	0,880	60 x 60 x 7	6,230
25 x 25 x 3,5	1,290	70 x 70 x 8	8,320
30 x 30 x 4	1,770	80 x 80 x 9	10,700
35 x 35 x 4,5	2,330	90 x 90 x 10	13,400
40 x 40 x 5	2,960	100 x 100 x 11	16,400
45 x 45 x 5,5	3,670	120 x 120 x 13	23,200
50 x 50 x 6	4,440	140 x 140 x 15	31,300



**EN 10025** Technische Lieferbedingungen  
**EN 10056** (DIN 1028) Maße und zulässige Abweichungen

## Winkelstahl, gleichschenkelig S235JR (W.-Nr. 1.0038)

Abmessung mm (b x s)	Gewicht kg/m	Abmessung mm (b x s)	Gewicht kg/m
20 x 3	0,880	60 x 10	8,690
4	1,140	65 x 6	5,910
25 x 3	1,120	7	6,830
4	1,450	8	7,730
5	1,770	9	8,620
30 x 3	1,360	70 x 6	6,380
4	1,780	7	7,380
5	2,180	9	9,340
35 x 3	1,600	11	11,200
4	2,100	75 x 7	7,940
5	2,570	8	9,030
6	3,040	10	11,100
40 x 3	1,840	80 x 7	8,490
4	2,420	8	9,660
5	2,970	10	11,900
6	3,520	12	14,100
45 x 4	2,740	90 x 8	10,900
5	3,380	9	12,200
6	4,000	11	14,700
7	4,600	13	17,100
50 x 4	3,060	100 x 8	12,200
5	3,770	10	15,100
6	4,470	12	17,800
7	5,150	14	20,600
8	5,820	16	23,200
9	6,470	110 x 10	16,600
55 x 5	4,180	12	19,700
6	4,950	14	22,800
8	6,460	120 x 11	19,900
60 x 5	4,570	12	21,600
6	5,420	13	23,300
8	7,090	15	26,600




Auch in S355J2 lieferbar.

# Stabstahl

**EN 10025** Technische Lieferbedingungen  
**EN 10056** (DIN 1028) Maße und zulässige Abweichungen

## Winkelstahl, gleichschenkelig, rundkantig S235JR (W.-Nr. 1.0038)




Auch in S355J2 lieferbar.

Abmessung mm (b x s)	Gewicht kg/m	Abmessung mm (b x s)	Gewicht kg/m
130 x 12	23,600	160 x 17	40,700
14	27,200	19	45,100
16	30,900	180 x 16	43,500
140 x 13	27,500	18	48,600
15	31,400	20	53,700
150 x 12	27,300	200 x 16	48,500
14	31,600	18	54,300
15	33,800	20	59,900
16	35,900	24	71,100
18	40,100	250 x 18	68,400
20	44,200	20	75,700
160 x 15	36,200	24	90,900

**EN 10025** Technische Lieferbedingungen  
**EN 10056** (DIN 1029) Maße und zulässige Abweichungen

## Winkelstahl, ungleichschenkelig, rundkantig S235JR (W.-Nr. 1.0038)



Auch in S355J2 lieferbar.


Abmessung mm (h x b x s)	Gewicht kg/m	Abmessung mm (h x b x s)	Gewicht kg/m
30 x 20 x 3	1,110	80 x 65 x 8	8,660
20 x 4	1,450	65 x 10	10,700
40 x 20 x 3	1,350	90 x 60 x 6	6,820
20 x 4	1,770	60 x 8	8,960
45 x 30 x 3	1,720	100 x 50 x 6	6,850
30 x 4	2,250	50 x 8	8,990
30 x 5	2,770	50 x 10	11,100
50 x 30 x 5	2,960	65 x 7	8,770
40 x 4	2,710	65 x 9	11,100
40 x 5	3,350	65 x 11	13,400
60 x 30 x 5	3,370	75 x 7	9,320
30 x 6	3,980	75 x 9	11,800
30 x 7	4,590	75 x 11	14,300
40 x 5	3,760	120 x 80 x 8	12,200
40 x 6	4,460	80 x 10	15,000
40 x 7	5,140	80 x 12	17,800
65 x 50 x 5	4,350	80 x 14	20,500
50 x 7	5,970	130 x 65 x 8	11,900
50 x 9	7,520	65 x 10	14,600
75 x 50 x 5	4,740	65 x 12	17,300
50 x 7	6,510	90 x 10	16,600
50 x 9	8,230	90 x 12	19,700
55 x 5	4,950	150 x 75 x 9	15,300
55 x 7	6,800	75 x 11	18,600
55 x 9	8,590	90 x 10	18,200
80 x 40 x 6	5,410	90 x 12	21,600
40 x 8	7,070	100 x 10	19,000
65 x 6	6,600	100 x 12	22,600

# Stabstahl

**EN 10025** Technische Lieferbedingungen  
**EN 10056 (DIN 1029)** Maße und zulässige Abweichungen

## Winkelstahl, ungleichschenkelig, rundkantig S235JR (W.-Nr. 1.0038)

Abmessung mm (h x b x s)	Gewicht kg/m	Abmessung mm (h x b x s)	Gewicht kg/m
150 x 100 x 14	26,100	200 x 100 x 12	27,300
160 x 80 x 10	18,200	100 x 14	31,600
80 x 12	21,600	100 x 16	35,900
80 x 14	25,000	250 x 90 x 10	26,100
180 x 90 x 10	20,600	90 x 12	31,100
90 x 12	24,500	90 x 14	36,000
90 x 14	28,300	90 x 16	40,900
200 x 100 x 10	23,000		




Auch in S355J2 lieferbar.

**EN 10025** Technische Lieferbedingungen  
**DIN 59200** Maße und zulässige Abweichungen

## Breitflachstahl S235JR (W.-Nr. 1.0038)

Abmessung mm (b x a)	Gewicht kg/m	Abmessung mm (b x a)	Gewicht kg/m
155 x 5	6,240	180 x 5	7,200
6	7,440	6	8,640
8	9,920	8	11,500
10	12,400	10	14,400
12	14,900	12	17,300
15	18,600	15	21,600
20	24,800	20	28,800
25	31,000	25	35,000
30	37,200	30	43,700
40	49,600	35	50,400
160 x 5	6,400	40	57,600
6	7,680	50	72,000
8	10,200	60	86,400
10	12,800	190 x 5	7,600
12	15,400	6	9,120
15	19,200	8	12,200
20	25,600	10	15,200
25	31,400	12	18,200
30	38,400	15	22,800
40	51,200	20	30,400
50	64,000	25	38,000
60	76,800	30	45,600
170 x 5	6,800	200 x 5	8,000
6	8,160	6	9,600
8	10,900	8	12,800
10	13,600	10	16,000
12	16,300	12	19,200
15	20,400	15	24,000
20	27,200	20	32,000
25	33,400	25	39,000
30	40,800	30	48,000
50	68,000	35	56,000



Auch in S355J2 lieferbar.




# Stabstahl

EN 10025  
DIN 59200

Technische Lieferbedingungen  
Maße und zulässige Abweichungen

## Breitflachstahl

S235JR (W.-Nr. 1.0038)



Auch in S355J2 lieferbar.

Abmessung mm (b x a)	Gewicht kg/m	Abmessung mm (b x a)	Gewicht kg/m
200 x 40	64,000	250 x 35	70,000
50	80,000	40	80,000
60	96,000	50	100,000
80	128,000	60	120,000
100	160,000	260 x 5	10,200
210 x 8	13,400	6	12,300
10	16,800	8	16,400
12	20,200	10	20,500
15	25,200	12	25,000
20	33,600	15	31,200
25	42,000	20	41,600
30	50,400	25	52,000
220 x 5	8,800	30	62,400
6	10,600	270 x 8	17,300
8	14,100	10	21,600
10	17,600	12	25,900
12	21,100	15	32,400
15	26,400	20	43,200
20	35,200	280 x 5	11,200
25	44,000	6	13,400
30	52,800	8	17,900
35	61,600	10	22,400
40	70,400	12	26,900
230 x 5	9,200	15	33,600
6	11,000	20	44,800
8	14,700	25	56,000
10	18,400	30	67,200
12	22,100	40	89,600
15	27,600	50	112,000
20	36,800	300 x 5	12,000
25	46,000	6	14,400
30	55,200	8	19,200
240 x 5	9,600	10	24,000
6	11,500	12	28,800
8	15,400	15	36,000
10	19,200	20	48,000
12	23,000	25	60,000
15	28,800	30	72,000
20	38,400	35	84,000
25	48,000	40	96,000
30	57,600	50	120,000
35	67,200	60	144,000
40	76,800	80	192,000
250 x 5	10,000	100	240,000
6	12,000	320 x 5	12,800
8	16,000	6	15,400
10	20,000	8	20,500
12	24,000	10	25,600
15	30,000	12	30,700
20	40,000	15	38,400
25	50,000	20	51,200
30	60,000	25	64,000

# Stabstahl


**EN 10025**  
**DIN 59200**

Technische Lieferbedingungen  
Maße und zulässige Abweichungen

**Breitflachstahl**

**S235JR (W.-Nr. 1.0038)**

Abmessung mm (b x a)	Gewicht kg/m	Abmessung mm (b x a)	Gewicht kg/m
320 x 30	76,800	400 x 5	16,000
320 x 40	102,000	400 x 6	19,200
330 x 10	26,400	400 x 8	25,600
330 x 12	31,700	400 x 10	32,000
330 x 15	39,600	400 x 12	38,400
330 x 20	52,800	400 x 15	48,000
330 x 25	66,000	400 x 20	64,000
330 x 30	79,200	400 x 25	80,000
340 x 8	21,800	400 x 30	96,000
340 x 10	27,200	400 x 40	128,000
340 x 12	32,600	400 x 50	160,000
340 x 15	40,800	400 x 60	192,000
340 x 20	54,400	450 x 6	21,600
340 x 25	68,000	450 x 8	28,800
340 x 30	81,600	450 x 10	36,000
340 x 40	109,000	450 x 12	43,200
350 x 5	14,000	450 x 15	54,000
350 x 6	16,800	450 x 20	72,000
350 x 8	22,400	450 x 25	90,000
350 x 10	28,000	450 x 30	108,000
350 x 12	33,600	450 x 40	144,000
350 x 15	42,000	500 x 5	20,000
350 x 20	56,000	500 x 6	24,000
350 x 25	70,000	500 x 8	32,000
350 x 30	84,000	500 x 10	40,000
350 x 40	112,000	500 x 12	48,000
350 x 50	140,000	500 x 15	60,000
350 x 60	168,000	500 x 20	80,000
360 x 8	23,000	500 x 25	100,000
360 x 10	28,800	500 x 30	120,000
360 x 12	34,600	500 x 40	160,000
360 x 15	43,200	500 x 50	200,000
360 x 20	57,600	500 x 60	240,000
360 x 25	72,000	600 x 6	28,800
360 x 30	86,400	600 x 8	38,400
360 x 40	115,000	600 x 10	48,000
380 x 10	30,400	600 x 12	57,600
380 x 12	36,500	600 x 15	72,000
380 x 15	45,600	600 x 20	96,000
380 x 20	60,800	600 x 25	120,000
380 x 25	76,000	600 x 30	144,000
380 x 30	91,200	600 x 40	192,000
380 x 40	122,000		




Auch in S355J2 lieferbar.

# Stabstahl

<b>EN 10025</b>	Technische Lieferbedingungen
<b>EN 10048 (DIN 1016)</b>	Maße und zulässige Abweichungen

## Bandstahl S235JR (W.-Nr. 1.0038)



Auch in S355J2 lieferbar.

Abmessung mm (b x a)	Gewicht kg/m	Abmessung mm (b x a)	Gewicht kg/m
10 x 2	0,157	40 x 3	0,942
3	0,236	4	1,260
4	0,314	45 x 3	1,060
12 x 2	0,189	4	1,410
3	0,283	50 x 3	1,180
4	0,377	4	1,570
15 x 2	0,230	55 x 3	1,300
3	0,353	4	1,730
4	0,471	60 x 2	0,942
16 x 2	0,250	3	1,410
3	0,377	4	1,880
4	0,502	70 x 3	1,650
18 x 3	0,425	4	2,200
4	0,565	80 x 3	1,880
20 x 1	0,157	4	2,510
2	0,314	90 x 3	2,120
3	0,471	4	2,820
4	0,628	100 x 3	2,350
25 x 1	0,196	4	3,140
2	0,393	110 x 3	2,590
3	0,589	4	3,450
4	0,785	120 x 3	2,820
30 x 1	0,236	4	3,760
2	0,471	130 x 3	3,060
3	0,707	4	4,080
4	0,942	140 x 3	3,280
35 x 3	0,824	4	4,400
4	1,100	150 x 3	3,530
40 x 2	0,628	4	4,710